



PYROFIL™ - Standard Spool Selection

Fiber Type	Number of Filaments	Spool Weight		Fiber Length		Size Levels %	Standard Case: Number of Spools	Standard Case: Approximate Net Weight (lbs)	Standard Pallet: Number of Cases	Standard Pallet: Approximate Net Weight (lbs)	Spool Outside Diameter	
		kg	lbs	meters	yards						mm	in
TR30S	3,000	1.00	2.20	5,000	5,468	1.2	18	39.60	12	475.20	104	4.09
TR50S	6,000	2.00	4.41	5,000	5,468	1.2	12	52.91	12	634.92	122	4.80
TR50S	12,000	4.00	8.82	5,000	5,468	0.4, 1.2	6	52.91	18	952.38	152	5.98
TR50S	15,000	5.00	11.02	5,000	5,468	1.0	6	66.14	18	1,190.52	170	6.69
TRH50	12,000	4.00	8.82	5,000	5,468	1.2	6	52.92	18	952.56	152	5.98
TRH50	18,000	5.00	11.02	5,000	5,468	1.0	6	66.14	18	1,190.52	170	6.69
TR330	50,000	8.00	17.64	2,500	2,734	1.0	4	75.00	12	900.00	210	8.27
MR40	12,000	1.50	3.31	2,500	2,734	0.4	12	39.72	12	476.64	122	4.80
MR60H	24,000	4.80	10.58	5,000	5,464	0.9	6	63.49	18	1,142.82	165	6.50

5900 88th Street
 Sacramento, CA
 95828, USA
 Tel: 916.386.1733
 Fax: 916.383.7668
 Web: www.grafil.com



ISO 9001:2000
 FM 56416

07/2008

6, Orchard Court
 Binley Business Park
 Harry Weston Road
 Binley, Coventry CV3 2TQ UK
 Tel: +44 (0) 2476 447272
 Fax: +44 (0) 2476 449565



PYROFIL™ - Standard Spool Selection

Fiber Type	Number of Filaments	Spool Weight		Fiber Length		Size Levels %	Standard Case: Number of Spools	Standard Case: Approximate Net Weight (lbs)	Standard Pallet: Number of Cases	Standard Pallet: Approximate Net Weight (lbs)	Spool Outside Diameter	
		kg	lbs	meters	yards						mm	in
MS40	12,000	1.50	3.31	2,500	2,734	0.4	12	39.72	12	476.64	122	4.80
HR40	12,000	1.50	3.31	2,500	2,734	0.4	12	39.72	12	476.64	122	4.80
HS40	12,000	1.08	2.38	2,500	2,734	0.4	12	28.57	12	342.84	113	4.45

Spool Core Dimensions: ID 3.0 in. (76mm), OD 3.2 in. (82mm), length 11.0 in. (280mm)

5900 88th Street
 Sacramento, CA
 95828, USA
 Tel: 916.386.1733
 Fax: 916.383.7668
 Web: www.grafil.com



ISO 9001:2000
 FM 56416

07/2008

6, Orchard Court
 Binley Business Park
 Harry Weston Road
 Binley, Coventry CV3 2TQ UK
 Tel: +44 (0) 2476 447272
 Fax: +44 (0) 2476 449565