



GRAFIL - Standard Spool Selection

Fiber Type	Number of Filaments	Spool Weight		Fiber Length		Size Levels %	Standard Case: Number of Spools	Standard Case: Approximate Net Weight (lbs)	Standard Pallet: Number of Cases	Standard Pallet: Approximate Net Weight (lbs)	Spool Outside Diameter	
		lbs	kgs	yards	meters						in	mm
34-700	12,000	5.0	2.25	3,060	2,800	1.2	9	45.0	24	1,080	5.4	137
		10.0	4.50	6,120	5,600	1.2	5*	50.0	24	1,200	6.9	175
34-700	24,000	5.0	2.25	1,530	1,400	1.2	9	45.0	24	1,080	5.5	140
		10.0	4.50	3,060	2,800	1.2	5*	50.0	24	1,200	7.0	178
34-700WD	12,000	5.0	2.25	3,060	2,800	0.7, 1.4	9	45.0	24	1,080	5.4	137
		10.0	4.50	6,120	5,600	0.7, 1.4	5*	50.0	24	1,200	6.9	175
34-700WD	24,000	5.0	2.25	1,530	1,400	0.7, 1.4	9	45.0	24	1,080	5.5	140
		10.0	4.50	3,060	2,800	0.7, 1.4	5*	50.0	24	1,200	7.0	178
34-600	48,000	5.0	2.25	765	700	1.2	9	45.0	24	1,080	5.6	142
		10.0	4.50	1,530	1,400	1.2	5	50.0	24	1,200	7.2	183
34-600WD	48,000	5.0	2.25	765	700	0.7, 1.4	9	45.0	24	1,080	5.6	142
		10.0	4.50	1,530	1,400	0.7, 1.4	5	50.0	24	1,200	7.2	183

Spool core dimensions ID 2.98 in. (75.55mm), OD 3.2 in. (82mm), length 11.75 in. (298 mm)

* Also available in pallet pack. A standard 3-layer pallet pack contains 42 spools per layer and has an approximate net weight of 1,260 lbs.

5900 88th Street
 Sacramento, CA
 95828, USA
Tel: 916.386.1733
Fax: 916.383.7668
Web: www.grafil.com



ISO 9001:2008
 FM 56416

03/2010

6, Orchard Court
 Binley Business Park
 Harry Weston Road
 Binley, Coventry CV3 2TQ UK
Tel: +44 (0) 2476 447272
Fax: +44 (0) 2476 449565